

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

ANYWHICHWAY

Anywhichway is a unique blend of textured and non-textured yarn. The style is characteristic of a natural woven appearance. Marling is using 100% solution dyed Nylon, with excellent colourfastness to light and cleaning solutions. The selection of natural colour tones makes this product suitable for today's modern office interior. The design in the tufting enables the tiles to be fitted in any pile direction hence its product name.

SPECIFICATION

| | |
|---------------------------------|----------------------------------|
| Construction | Tufted |
| Description | FRS Textured Loop Pile |
| Fibre Type | 100% Solution dyed Polyamide 6,6 |
| Pile weight | 780gm ² +/-10% |
| Tufting gauge | 1/12th |
| Tuft density per m ² | 186,283 per m ² |

SHEET

| | |
|-------------------|---------------------|
| Primary backing | Non Woven polyester |
| Secondary backing | Unitary |

TILES

| | | |
|---------------------------|-----------------------------|-----------------------------|
| Primary backing | Non-Woven Polyester | |
| Secondary backing | Glass re-enforced Bitumen | Acoustic Felt |
| Total weight | 4620gm ² +/- 10% | 4450gm ² +/- 10% |
| Pile Height | 4.5mm +/-1mm | 4.5mm +/-1mm |
| Total thickness tiles | 8.5mm +/-1mm | 11.5mm +/-1mm |
| Total thickness broadloom | 6mm +/-1mm | |

Availability

| | | |
|--------------|---------------|---------------|
| Broadloom | 25m x 2m | |
| Carpet tiles | 500mm x 500mm | 500mm x 500mm |

PERFORMANCE

| | |
|-------------------------------|--|
| Wear rating | Extra heavy contract |
| Castor chair DIN 54324 | Pass |
| Electrostatic properties | Stroll test <2000 volts |
| IBM/ICL test | Pass at 40% Rh |
| Flammability | BS 4790 Low radius of ignition |
| NBS Radiant Panel | ASTM E648 class 1 |
| Colour Fastness BS EN ISO 105 | Light 6-7 Water 5-6 Wet/dry 5-6 Shampoo 5-6 |

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction. Carpet in the same room/area must be from the same dye-batch (given on the label of the roll or box). Observe consistent pile direction.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48x or Laybond 47.

Release System Selected carpets may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Camouflage dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System. We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to be colour matched should be ordered and fitted at the same time. Please allow for possible variation in supplied material.