

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

BURFORD TILE

Burford is a competitively priced nylon loop pile tile, ideal for restrained budgets. Burford is made from solution dyed nylon, which is colour fast, stain resistant and bleach proof. Colour is locked in making cleaning and maintenance extremely straight forward. Burford with its tight low level loop is eminently suitable for all commercial applications including offices, schools, universities and public buildings.

Specification

Construction	Tufted
Description	Loop pile
Fibre type	100% Nylon 6
Dyeing method	Solution Dyed
Tufting gauge	1/10 th
Tuft density	171260m ²
Pile weight	500g/m ² +/-10%
Primary backing tiles	Non-Woven Polyester
Secondary backing tiles	Glass re-inforced Bitumen
Total weight	4340g/m ² +/-10%
Pile Height	3.5mm +/-1mm
Total thickness tiles	6.5mm +/-1mm
Total thickness broadloom	N/A
Availability	
Broadloom	N/A
Carpet tiles	500mm x 500mm
Colours	12

PERFORMANCE

Wear rating	Heavy Contract
Castor chair BS EN 985	Pass r = 2.8
Electrostatic properties	Stroll test <2000 volts
IBM/ICL test	Pass at 40%
Flammability BS 4790	Low radius of char
NBS Radiant Panel	ATM E648 class 1
Colour Fastness BS EN ISO 105	Light 6 Water 5 Wet/dry4-5 Shampoo 4-5

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction. Carpet in the same room/area must be from the same dye-batch (given on the label of the roll, or box). Observe consistent pile direction.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48 xs or Laybond 47.

Release System Selected carpets may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Camouflage dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System. We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to colour matched should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

* Full details of our Limited Wear Warranties are available on request.