

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

Camouflage Entrance Matting

Marlings Camouflage Entrance Matting uses coarse filament yarn providing enhanced removal of dirt by abrasion, as well as by absorption of wet soiling. The benefits of this system are as follows:

Enhanced appearance retention from existing floor coverings, Lower maintenance costs and improved safety.

Specification

Product	Camouflage Entrance Matting
Construction	Tufted
Description	Cut Pile Patterned
Fibre type	100% Nylon
Dyeing method	Solution Dyed/Packaged Dyed
Tufting gauge	1/8 th
Tuft density	102000 +/- 10%
Pile weight	1200 g/m ² +/- 10%
Primary backing tiles	Non-woven polyester
Secondary backing tiles	Glass re-inforced bitumen
Total weight Tiles	5138g/m ²
Pile Height	7mm +/-0.5mm
Total thickness tiles	10mm +/-0.5mm

Availability

Carpet tiles	500mm x 500mm
Colours	5

PERFORMANCE

Wear rating	Heavy Contract
Castor chair DIN 54324	N/A
Electrostatic properties	Stroll test <2000 volts
IBM/ICL test	N/A
Flammability BS 4790	Low radius of char
NBS Radiant Panel	N/A
Colour Fastness BS EN ISO 105	Light 6-7 Water 5-6 Wet/dry 5-6 Shampoo 5-6

Warranties

10 Year*

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof sub floor, and to the adhesive manufacturer's instruction.

Carpet in the same room/area must be from the same dye-batch (given on the label of the roll, or box). Observe consistent pile direction. Linear effect designs, and cord carpet tiles must be fitted in a ¼ turn or chequerboard fashion, Diminishing strips are recommended where different heights of carpet tiles are apparent.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48 xs or Laybond 47.

Release System Camouflage Primary Matting System may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Deep clean periodically using the Texatherm Cleaning System. We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to colour matched should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

*Full details of Limited Wear Warranties are available on request.