

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse  
Gloucestershire GL10 3HQ

## CHEDWORTH

**CHEDWORTH** is a heavy contract cut-pile velour carpet, available as tiles or 4m broadloom, suitable for commercial or institutional use.

### SPECIFICATION

<b>Construction</b>		Cut pile
<b>Pile composition</b>		100% Antron nylon with Bayer antisoil treatment
<b>Gauge</b>		1/10" (39 tufts per 10 cm)
<b>Tuft density</b>		300,200 tufts per m <sup>2</sup> nominal
<b>Pile mass/unit area</b>		770 g/m <sup>2</sup> nominal
<b>Primary backing</b>		No woven polyester
<b>Secondary backing</b>	<b>broadloom</b>	Woven
	<b>tile:</b>	Antistatic Reinforced bitumen/ PVC
<b>Total mass/unit area</b>	<b>broadloom</b>	1650 g/m <sup>2</sup> nominal
	<b>tile:</b>	4500 g/m <sup>2</sup> nominal – check!
<b>Pile height</b>		4 mm
<b>Total thickness</b>		7 mm
	<b>broadloom</b>	8 mm
	<b>tile:</b>	
<b>Availability</b>		Broadloom and tile
<b>Dimensions</b>	<b>broadloom</b>	25m x 4m
	<b>Tile:</b>	500 x 500 mm (20 tiles per box) 600 X 600
<b>Colours</b>		16

### PERFORMANCE

<b>Wear rating</b>	Heavy contract
<b>Castor chair</b>	Pass

### TECHNICAL PROPERTIES

<b>Static electricity</b>	Stroll test < 2000 volts permanent antistatic	<b>IBM / ICL</b> Pass
<b>Flammability BS 4790</b>	Low radius of char	
<b>Fastness BS EN ISO 105</b>	Light 5      Water 4 Wet/dry rubbing 4	

### INSTALLATION

Lay on smooth, clean, dry and damp-proof sub floor using a suitable all-over adhesive. Carpet in the same room/area must be from the same dye batch (given on the roll or box label). Observe consistent pile direction. Pads and tiles are best laid chequerboard. Installation must be in accordance with BS5325 "Code of practice for the installation of textile floor coverings" and the adhesive manufacturer's instructions.

**Sheet** Fully bond using a suitable adhesive such as F Ball's F3.

**Tile** Use an all-over tackifier such as F Ball's F41.

### MAINTENANCE

Vacuum daily using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Warlord dirt barrier matting adjacent to entrances. Deep clean periodically using dry foam or spray extraction method. We recommend the use of castor chair mats where appropriate.