

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

Delta Plus

DELTA PLUS is a computer-antistatic heavy contract flat needlepunch carpet, suitable for commercial or institutional use on solid subfloors or raised flooring systems.

SPECIFICATION

Pile Composition	70% Polypropylene 30% Nylon
Pile Weight	730 g/m ²
Total Weight	900 g/m ² ± 10%
Nominal Thickness	5 mm ± 10%
Colours	9 (specials 500m ² +)

PERFORMANCE

Wear Rating	Heavy Contract
Castor Chair BS EN 985	Pass
Static Loading BS 4939	Loss / 24 hours: 1.1mm
Dynamic Loading BS 4052	Loss / 1000 impacts: 1.2mm
Hexapod Test BS 6659	Structure Change: 3-4

TECHNICAL PROPERTIES

Static Electricity:	Stroll Test <2000 volts
	IBM / ICL Test: Within upper / lower limits
Flammability BS 4790	Low radius of char
Fastnesses BS EN ISO 105	Light 5-6 Water 5 Wet/Dry 5 Shampoo 5

AVAILABILITY

Sheet:	25m x 2m
Pad	500mm X 500mm, 615mm X 615mm

INSTALLATION

Sheet Fully bond using suitable adhesive such as F Ball's F3