

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

DURSLEY

DURSLEY is an attractive multicoloured low-level loop pile carpet tile, in 100 percent polyamide. The exciting range of colours meets the discerning specifier's requirements for serviceability and aesthetics. With the added bonus of a well integrated combination of colour and structure, allowing a monolithic finish in the way the tiles are installed, rather than installing in the checkerboard methods.

SPECIFICATION

Construction	Tufted
Description	Loop pile
Fibre type	100% BCF Nylon 6
Dyeing method	Spaced dyed
Tufting gauge	1/10
Tuft density (nominal)	173,000
Primary backing	Non – woven Polyester
Secondary backing	Glass reinforced bitumen
Pile weight (nominal)	530 g/m ² ± 5%
Pile height (nominal)	4.2 mm ± 0.5mm
Total thickness	6.7 mm ± 10%
Total tile weight	4370 g/m ² ± 10%
Availability	
Carpet tiles	500mm x 500mm
Colours	10

PERFORMANCE

Wear rating	Heavy Contract Class 4
Castor chair	Pass over r value 2.9
Electrostatic properties	
Stroll test	<2000 volts
Flammability BS 4790	Low radius of ignition
NBS Radiant Panel ASTM E648	Class 1
Acoustic Properties	23dB
Colour fastness BS EN ISO 105	Light 5 water 4-5 Wet/dry 4/5 Shampoo 4/5

INSTALLATION

All products should be installed to BS5325 and CFA guidelines lay on smooth, clean, dry and damp-proof subfloor. Carpet in the same room/area must be from the same dye batch (given on the roll or box label). Observe consistent pile direction. Installation must be in accordance with BS5325 "Code of practice for the installation of textile floor coverings" and the adhesive manufacturer's instructions.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold.

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48x or Laybond 47.

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Warlord dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System **we recommend the use of castor chair mats.**

Marlings Ltd reserves the right to change or modify specifications
PS 43 Issue 3