

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

FROME TILE

Frome is a budget- conscious medium contract carpet tile suitable for domestic and general use. The loop pile construction gives good wear performance; the polypropylene yarn imparts stain-resistance and easy-clean properties; and the bitumen backing gives weight and stability to the product

SPECIFICATION

Construction	Tufted
Description	Loop Pile
Fibre Type	100% polypropylene
Pile weight	370 gm ² +/-5%
Tufting gauge	1/10th
Primary backing	Non-Woven Polyester
Secondary backing	Glass reinforced bitumen
Total weight	4180 gm ² /+/-10%
Pile Height	3mm +/- 0.5mm
Total thickness	5.9mm +/-10%
Carpet tiles	500mm x 500mm
Tiles per box	20 tiles = 5 sqm

PERFORMANCE

Wear rating	Domestic / general use
Electrostatic properties	Stroll test <3000 volts
Flammability	Low radius of ignition
Colour Fastness BS 1006	Light 5-6 Water 4-5 Wet/dry 5 Shampoo 4-5

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction. Carpet in the same room/area must be from the same dye-batch (given on the label of the roll or box). Observe consistent pile direction.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48x or Laybond 47.

Release System Selected carpets may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Camouflage dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to colour matched should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

* Full details of Limited Wear Warranties are available on request.