

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

Livingston

Livingston carpet tile from Marlings is a high performance contract loop pile. The construction is made of top quality Polyamide Nylon. Livingston has superb technical performance with a wide range of colour choice.

SPECIFICATION	Livingston
Construction	Tufted
Description	Loop Pile
Fibre type	100% Polyamide
Dyeing method	Solution Dyed
Tufting gauge	1/12 th
Tuft density	181,400 m ²
Pile weight	608 g/m ² ± 5%
Primary backing tiles	Non-Woven Polyester
Secondary backing tiles	Glass re-inforced Bitumen
Total weight	4443 g/m ² ± 5%
Pile Height	3.8mm ± 0.1mm
Total thickness tiles	7.3mm ± 0.5mm
Availability	
Carpet tiles	500 x 500mm ± 0.2%
Colours	

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction.

Carpet in the same room/area must be from the same dye-batch (given on the label of the roll, or box). Observe consistent pile direction.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48x or Laybond 47.

Release System: Selected carpets may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush, which contacts the pile. Treat spots and spillages immediately. Use Camouflage dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System. We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to colour match should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

Marlings Ltd reserves the right to change or modify specifications
PS 19 Issue 2