

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

MONTROSE TILE

Montrose is loose-lay tile suitable for heavy contract use. The loop pile construction gives good wear performance; the polypropylene yarn fibre imparts stain-resistance and easy-clean properties; and the bitumen backing gives stability to the whole.

SPECIFICATION

Construction	Loop pile tufted (1/10 gauge)
Fibre type	100% polypropylene
Tile backing	Glass reinforced oxidised bitumen
Secondary backing	Spun bonded polypropylene
Tuft density per sqm	165,000
Pile weight (nominal)	550 gm/sqm
Total weight (nominal)	4390 gm/sqm
Pile height (nominal)	3.5mm
Total thickness (Bitumen)	7mm
Tile size	500mm x 500mm (600 x 600mm to special order)

PERFORMANCE

Wear Rating	Heavy contract
Static electricity	Stroll test < 2000 volts
Flammability BS 4790	Low radius of char
Colour Fastness BS 1006	Light >6 Water 4-5 Wet/Dry 4-5 Shampoo 4-5

INSTALLATION

Tiles should be laid on a smooth dry subfloor using an all-over application of a suitable tackifier adhesive, such as F Ball's F41. Tiles in the same room/area must be from the same dye batch (indicated on the box and on the back of the tile)/

Tiles may be fitted to special order with magnetic strips to secure the tiles to metal-faced floor panels.