

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

NATURALS

Naturals is a unique blend of textured and non-textured yarn. The style is characteristic of a natural woven appearance Marling is using 100% solution dyed Nylon, with excellent colourfastness to light and cleaning solutions. The selection of natural colour tones makes this product suitable for today's modern office interior.

SPECIFICATION

Construction	Tufted	
Description	FRS Textured Loop Pile	
Fibre Type	100% Solution dyed Polyamide 6,6	
Pile weight	780gm ² +/-10%	
Tufting gauge	1/12th	
Tuft density per m ²	186,283 per m ²	
SHEET		
Primary backing	Non Woven polyester	
Secondary backing	Unitary	
TILES		
Primary backing	Non-Woven Polyester	
Secondary backing	Glass re-inforced Bitumen	Acoustic Felt
Total weight	4620gm ² +/- 10%	4450gm ² +/- 10%
Pile Height	4.5mm +/-1mm	4.5mm +/-1mm
Total thickness tiles	8.5mm +/-1mm	11.5mm +/-1mm
Total thickness broadloom	6mm +/-1mm	
Availability		
Broadloom	25m x 2m	
Carpet tiles	500mm x 500mm	500mm x 500mm

PERFORMANCE

Wear rating	Extra heavy contract	
Castor chair DIN 54324	Pass	
Electrostatic properties	Stroll test <2000 volts	
IBM/ICL test	Pass at 40% Rh	
Flammability	BS 4790 Low radius of ignition	
NBS Radiant Panel	ASTM E648 class 1	
Colour Fastness BS EN ISO 105	Light 6-7	Water 5-6
	Wet/dry 5-6	Shampoo 5-6

INSTALLATION

All products should be installed to CFA guidelines and BS5325 "Code of Practice for the Installation of Textile Floor Coverings". Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction. Carpet in the same room/area must be from the same dye-batch (given on the label of the roll or box). Observe consistent pile direction.

Tiles: Apply an all-over coating of a pressure sensitive adhesive such as Laybond 79.

Sheet/Broadloom (Tufted) fully bond using a suitable adhesive such as Laybond Multibond Gold or CV

Sheet/Broadloom (Fibre-bonded) fully bond using a suitable adhesive such as Laybond 48x or Laybond 47.

Release System Selected carpets may be installed using a Pressure Sensitive Adhesive such as Multi-Tack

MAINTENANCE

Vacuum daily, using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Camouflage dirt barrier matting adjacent to entrances. Deep clean periodically using the Texatherm Cleaning System We recommend the use of castor chair mats.

N.B It is not possible to colour match from different dye batches and blends of yarn. Areas that need to colour matched should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

* Full details of Limited Wear Warranties are available on request.