

Tel: 01453 821800

Fax: 01453 791167

Email: sales@marlingscarpets.co.uk

Website: www.marlings.co.uk



Marlings

Marlings Limited

Stanley Mills Stonehouse
Gloucestershire GL10 3HQ

TRIDENT

Trident Broadcord is a computer antistatic heavy contract ribbed needlepunch carpet suitable for commercial use on solid subfloors or raised flooring systems.

SPECIFICATION

Construction	80% Polypropylene 20% Nylon
Fibre type	Needlepunch
Tufting gauge	N/A
Tuft density (nominal)	N/A
Primary backing	N/A
Secondary backing (tiles)	Reinforced Bitumen
Secondary backing (broadloom)	N/A
Pile weight (nominal)	900g/m ²
Total weight	1100g/m ²
Pile height (nominal)	7mm
Total thickness (tiles)	7.5mm
Total thickness (broadloom)	7mm
Availability	
Carpet tiles	500x500mm
Broadloom	25 x 2m
Colours	12

PERFORMANCE

Wear rating	Heavy Contract
Castor chair	2.4 (pass)
Electrostatic properties	
Stroll test	<2000 volts
Flammability	
BS 4790	Low radius of char
Colour fastness BS EN ISO 105	Light 5-6 Water 5 Wet/Dry 5 Shampoo 5

All products should be installed to BS5325 and CFA guidelines. Detailed fitting instructions are available from Warlord, please contact at the address below. Warlord reserves the right to change or modify specifications.

INSTALLATION

Tiles: Lay on smooth, clean, dry and damp-proof subfloor using an all-over coating of a pressure sensitive adhesive such as Laybond 79. Carpet in the same room/area must be from the same dye batch (given on the roll or box label). Observe consistent pile direction. Installation must be in accordance with BS5325 "Code of practice for the installation of textile floor coverings" and the adhesive manufacturer's instructions.

Sheet/Broadloom Fully bond using a suitable adhesive such as Laybond Multibond Gold.

MAINTENANCE

Vacuum daily using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Use Warlord dirt barrier matting adjacent to entrances. Deep clean periodically using dry foam or spray extraction method. We recommend the use of castor chair mats.

For larger samples or further advice on installation or maintenance, please contact the Sales Department at the address on the below.